

Specifications

2 ft Rotundita (Round) Stardome™

Physical

- **Material** Fiberglass/Polyester Layup (FRP)
- **Finish (concave dome surface):** Latex and Acrylic Sky Painting
- **Finish (cove and trim ring):** Sanded White Polyester Gelcoat
- **Overall Dimensions:** 28" x 28" x 5"
- **Dome Dimensions:** 23-1/2" x 3-1/2"
- **Minimum Dome Recess:** 4-1/2 inches
- **Trim Ring Thickness:** N/A
- **Dome Concave Area:** 3.6 sq. ft.
- **Dome Weight (typical):** 10 lbs
- **Number of Stars (standard)** 75
- **Storage/Operating Temperature** 40 - 120°F

Power

- **Supply** 110 – 120 VAC, 60Hz
- **Star Light Source Consumption** 1 Watt
- **Cove Light Consumption** 33 Watts (full brightness)

Operation

- **Stars** On/Off switch
- **Cove light** Dimmer Switch

Maintenance

- **Twinkling star light source has a rated life of 100,000 hours. Is easily replaceable.**
- **Cove light has a rated life of 25,000 hours. Is easily replaceable.**
Note: Unlike other StarDomes, The Rotundita must be removable from its installation for service from the back side.

Options

- **Two Configurations:** Overhead StarDome or wall-mounted Space Portal
- **Custom Paint (concave dome surface only)**
- **Additional Stars**
- **Class A Fire and Smoke rating per ASTM E84**
- **9" Shooting Star**
- **Wooden Case for surface mount or portable display**

Regulatory

- **UL Approved, File # E246977; Furnishings, Household and Commercial**

Contact Numinus, LLC 1-888-611-3663.