Specifications, 6’ Rotunda (Round) Stardome™

Physical

Material	Fiberglass/Polyester Layup (FRP)
Finish (concave dome surface):	Latex and Acrylic Sky Painting
Finish (cove and trim ring):	Sanded White Polyester Gelcoat
Overall Dimensions:	78-3/8” dia. x 11-3/4
Dome Dimensions:	70-1/2” dia.
Minimum Dome Recess:	9-7/8 inches
Trim Ring Thickness:	1-3/8 inches
Dome Concave Area:	35 sq. ft.
Dome Weight (typical):	55 lbs (plus trim ring, 8 lbs)
Number of Stars (standard)	170
Storage/Operating Temperature	40 - 120°F

Power

Supply	110 – 120 VAC, 60Hz
Star Light Source Consumption	2 Watts
Cove Light Consumption	46 Watts (full brightness)

Operation

Stars	On/Off switch
Cove light	NuLEDs SD232 LED Controller

Maintenance

- **Twinkling star light source has a rated life of 50,000 hours. Is easily replaceable.**
- **Cove light has a rated life of 50,000 hours. Is easily replaceable.**

Options

- **Custom Star field (requires date, time, location)**
- **Additional Stars**
- **Class A Fire and Smoke rating per ASTM E84**
- **28” Shooting Star**

Regulatory

- **UL Approved, File # E246977; Furnishings, Household and Commercial**

Contact Numinus, LLC 1-888-611-3663.

Copyright © 2006-2011 Numinus, LLC www.numinus.com