

Specifications

6' x 9' Oval Grande Stardome™

Physical

- **Material** Fiberglass/Polyester Layup (FRP)
- **Finish (concave dome surface):** Latex and Acrylic Sky Painting
- **Finish (cove and trim ring):** Sanded White Polyester Gelcoat
- **Overall Dimensions:** 114-3/8" x 78-3/8" x 13-1/2"
- **Dome Dimensions:** 106-1/2" x 70-1/2"
- **Minimum Dome Recess:** 12 inches
- **Trim Ring Thickness:** 1-1/2 inches
- **Dome Concave Area:** 50 sq. ft.
- **Dome Weight (typical):** 65 lbs (plus trim ring, 10 lbs)
- **Number of Stars (standard)** 185
- **Storage/Operating Temperature** 40 - 120°F

Power

- **Supply** 110 – 120 VAC, 60Hz
- **Star Light Source Consumption** 2 Watts
- **Cove Light Consumption** 500 Watts (full brightness)

Operation

- **Stars** On/Off switch
- **Cove light** Dimmer Switch

Maintenance

- **Twinkling star light source has a rated life of 100,000 hours. Is easily replaceable.**
- **Cove light has a rated life of 25,000 hours. Is easily replaceable.**

Options

- **Custom Paint (concave dome surface only)**
- **Custom Star field (requires date, time, location)**
- **Additional Stars**
- **Class A Fire and Smoke rating per ASTM E84**
- **28" Shooting Star, Moon**

Regulatory

- **UL Approved, File # E246977; Furnishings, Household and Commercial**

Contact Numinus, LLC 1-888-611-3663.